

## G-Energy Racing 10W-60, 15W-50



Engine oil



Fully synthetic base (PAO + esters)



Multigrade, SAE 10W-60, 15W-50



High engine cleanliness



For gasoline and diesel engines



Racing mode



High engine protection

**G-Energy Racing** - fully synthetic (PAO and esters) motor oils designed to maximize the protection of gasoline and diesel engines of racing, sports, and specialized vehicles operating under harsh operating conditions. The oils can withstand very high thermal loads and extreme operating conditions of sports competitions, while ensuring full engine performance

### Application



- Designed for use in all types of sports engines (gasoline, diesel, turbocharged, direct-injection, carburetor)
- Designed specifically for professional use in various types of automotive competitions
- Designed for use in boosted sports car engines where API SP; SN; ACEA A3/B4 or earlier API SM, API SL specifications are required

### Advantages

The unique synthetic technology (PAO and esters) series of oils G-Energy Racing ensures reliable engine operation in the most highly accelerated operating modes:

	Provides maximum overhaul mileage due to excellent anti-wear properties
	High engine performance due to reduced friction and esters in the composition
	Provides reliable engine operation under forced operation due to particularly strong oil film and stable viscosity
	Keeps engine parts clean by preventing deposit formation and high cleaning properties

## Specifications

- API SP; SN
- ACEA A3/B4
- Fiat 9.55535-H3 (10W-60)

## Typical characteristics

Properties	Values		Method
	10W-60	15W-50	
Kinematic Viscosity, mm <sup>2</sup> /s at 40 °C at 100 °C	163,5 24,6	140,15 20,75	ASTM D 445 ASTM D 445
Viscosity Index	184	173	ASTM D 2270
Flash Point (COC), °C	230	227	ASTM D 92
Pour Point, °C	-50	-50	ASTM D 97
Density at 15 °C, kg/m <sup>3</sup>	855	855	ASTM D 1298
Total Base Number, mg KOH/g	11,5	10,7	ASTM D 2896
NOACK, %	8,6	8,4	ASTM D 5800

## Certified

ISO 9001



ISO 14001



ISO 45001

