

## Gazpromneft Standard 10W-40, 15W-40, 20W-50



Engine oils



Mineral oils



Multigrade oils



For gasoline and diesel engines



Maintains pressure in the Lubrication System

Gazpromneft Standard – range of all-season, multipurpose engine oils designed for use in high-mileage carbureted gasoline and naturally aspirated diesel engines of passenger vehicles operating under various conditions. Gazpromneft Standard oils help maintain the required oil pressure in high-mileage engines. The additional inclusion of anti-wear and detergent additives provides enhanced protection against wear and deposit formation in aged engines.

### Advantages

- Extends the service life of high-mileage engines due to a durable oil film
- Maintains oil pressure in the lubrication system of high-mileage engines
- Reduces the risk of oil leaks thanks to compatibility with seal materials
- Protects high-mileage engines from wear and corrosion when oil change intervals are observed as recommended

### Application



- Passenger cars, light SUVs, vans, and light trucks with high mileage.
- Intended for carbureted gasoline and naturally aspirated diesel engines in vehicles requiring API SF, CC or earlier performance levels.

Specifications	Gazpromneft Standard		
	10W-40	15W-40	20W-50
API SF	✓	✓	✓
API CC	✓	✓	✓
PJSC AVTOVAZ	✓	✓	✓

## Standard physico-chemical characteristics

Indicators	Method	Gazpromneft Standard		
		10W-40	15W-40	20W-50
Kinematic viscosity, mm <sup>2</sup> /s: at 100 °C at 40 °C	ASTM D 445	94,5 13,9	103,7 14,1	164,5 18,3
Viscosity index	ASTM D 2270	157	139	121
Flash point, COC (Cleveland Open Cup Flash Tester), °C	ASTM D 92	226	230	245
Pour point, °C	ASTM D 97	-41	-38	-32
Base number, mg KOH/g	GOST 11362	7,0	6,9	8,0
Density at 20 °C, kg/m <sup>3</sup>	ASTM D 4052	871	875	885
Sulfated ash, %	ASTM D 847	0,8	0,8	0,9

The company's management system is certified in accordance with the international standards

ISO 9001



ISO 14001



ISO 45001

