

## Gazpromneft Super 10W-30, 10W-40, 15W-40



Engine oils



Semi-synthetic oil  
(10W-40)



Mineral oils  
(10W-30; 15W-40)



Multigrade oils



For gasoline and diesel  
engines



Extends the service life of  
high-mileage engines

Gazpromneft Super – range of all-season, multipurpose engine oils designed for gasoline and diesel engines of high-mileage passenger vehicles operating under various conditions.

Gazpromneft Super oils ensure reliable engine performance and help extend engine life. The inclusion of additional anti-wear and detergent additives provides enhanced protection for high-mileage engines against wear and deposit formation.

### Advantages

- Maintains oil pressure in the lubrication system of high-mileage engines
- Compatible with sealing materials, reducing the risk of oil leaks
- Supports the performance of high-mileage engines through a specially selected additive package
- Protects high-mileage engines from wear and corrosion when oil change intervals are observed as recommended

### Application



- Passenger cars, light SUVs, vans, and light trucks with high mileage.
- Designed for gasoline and diesel engines (turbocharged and naturally aspirated), requiring API SG, CD or earlier performance levels.

Specifications	Gazpromneft Super		
	10W-40	10W-30	15W-40
API SG	✓	✓	✓
API CD	✓	✓	✓
PJSC AVTOVAZ	✓	✓	✓

## Standard physico-chemical characteristics

Indicators	Method	Gazpromneft Super		
		10W-40	10W-30	15W-40
Kinematic viscosity, mm <sup>2</sup> /s: at 100 °C at 40 °C	ASTM D 445	95,1 14,1	76,8 11,5	107,2 14,5
Viscosity index	ASTM D 2270	155	145	139
Flash point, COC (Cleveland Open Cup Flash Tester), °C	ASTM D 92	227	237	235
Pour point, °C	ASTM D 97	-40	-38	-39
Base number, mg KOH/g	GOST 11362	8,7	7,0	10,0
Density at 20 °C, kg/m <sup>3</sup>	ASTM D 4052	869	871	878
Sulfated ash, %	ASTM D 847	1	1	1

The company's management system is certified in accordance with the international standards

ISO 9001



ISO 14001



ISO 45001

