

## Gazpromneft Super 5W-30, 5W-40



Engine oils



Synthetic Oil



Extends the service life of high-mileage engines



Multigrade oils



For gasoline and diesel engines



Excellent low-temperature properties

Gazpromneft Super – range of multigrade synthetic engine oils designed for use in gasoline and diesel engines of high-mileage passenger vehicles operating under various conditions. Gazpromneft Super oils ensure reliable engine performance and help extend engine life. The inclusion of additional anti-wear and detergent additives provides enhanced protection for high-mileage engines against wear and deposit formation.

### Advantages

- Maintains oil pressure in the lubrication system of high-mileage engines
- Compatible with sealing materials, reducing the risk of oil leaks
- Improved low-temperature properties
- Supports the performance of high-mileage engines through a specially selected additive package
- Protects high-mileage engines from wear and corrosion when oil change intervals are observed as recommended

### Application



- Passenger cars, light SUVs, vans, and light trucks with high mileage.
- Designed for gasoline and diesel engines (turbocharged and naturally aspirated), requiring API SG, CD or earlier performance levels.

Specifications	Gazpromneft Super	
	5W-30	5W-40
API SG	✓	✓
API CD	✓	✓
PJSC AVTOVAZ	✓	✓

## Standard physical and chemical characteristics

Indicators	Method	Gazpromneft Super	
		5W-30	5W-40
Kinematic viscosity, mm <sup>2</sup> /s: at 40 °C at 100 °C	ASTM D 445	70,1 11,8	90,6 14,5
Viscosity index	ASTM D 2270	160	167
Flash point, COC, °C	ASTM D 92	234	226
Pour point, °C	ASTM D 97	-43	-40
Base number, mg KOH/g	GOST 11362	8,1	8,1
Density at 20 °C, kg/m <sup>3</sup>	ASTM D 4052	849	850
Sulfated ash, %	ASTM D 847	1	1

The company's management system is certified in accordance with the international standards

ISO 9001



ISO 14001



ISO 45001

