

Gazpromneft Motor Oil 40, 50, 60



Engine oil



Liquid fuel
operation



High quality
mineral oil

Gazpromneft Motor Oil – series of summer universal engine oils, intended for use in gasoline and diesel engines of light vehicles operating in hot climate conditions. Developed with the use of high quality mineral base oils. Due to excellent stability of oil film provide reliable wear protection of the engine parts.

Advantages

- Engine protection in condition of high ambient air temperatures due to viscosity stability
- Compatibility with the sealing materials provides reducing the likelihood of leakage
- Engine protection against deposits due to high thermal- oxidation stability

Applications



- Passenger cars, light SUVs, vans, small trucks with high mileage.
- For gasoline and diesel engines (with and without turbocharging) where API SC, CA and lower performance level is required, as well as corresponding viscosity class SAE 40, 50, 60

Specifications	Gazpromneft Motor oil		
	40	50	60
API SC	✓	✓	✓
API CA	✓	✓	✓

Typical physical and chemical characteristics

Parameters	Method	Gazpromneft Motor Oil		
		40	50	60
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	168,4	231,7	359,2
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	15,3	19,0	25,0
Flash Point (COC), °C	ASTM D92	246	255	284
Pour Point, °C	GOST 20287	-13	-11	-12
Total Base Number, mg KOH/g	GOST 11362	4,8	4,6	4,7
Density @20°C, kg/m ³	ASTM D4052	884	896	900

The company's management system is certified in accordance with the international standards

ISO 9001



ISO 14001



ISO 45001

