



## Gazpromneft Premium L 5W-30, 5W-40, 10W-30, 10W-40, 15W-40, 20W-50



Engine oils



Synthetic Oils (SAE 5W-30, 5W-40, 10W-30, 10W-40)



Mineral oils (SAE 15W-40, 20W-50)



Gasoline and diesel engines



Multigrade (All-season) oils



Special polymeric molecules

Gazpromneft Premium L – series of universal multigrade engine oils, designed for maximum protection of gasoline and diesel engines of passenger cars, working in various operating conditions. Oils provide engine cleanliness and high wear protection in accordance with the requirements of car manufacturers.

## **Advantages**

- Maintain cleanliness of engine components due to preventing of deposit formation and high detergent properties
- Reliable cold engine starting when using SAE 5W-30 and 5W-40 oils due to high pumpability at low temperatures
- Possibility to use in a wide range of ambient temperatures due to the availability of different viscosity grades in the product line
- Excellent engine protection due to specialized polymer molecules that maintain a durable oil film

## **Applications**



- Passenger cars, off-road vehicles, vans, and light trucks of European and other manufacturers
- Designed for gasoline and diesel engines (turbocharged and non-turbocharged) of a wide fleet of vehicles where
  API SL, CF performance level and lower is required

	Gazpromneft Premium L							
Specifications	5W-40	5W-30	10W-40	10W-30	15W-40	20W-50		
API SL	✓	<b>√</b>	✓	<b>√</b>	<b>√</b>	✓		
API CF	<b>√</b>	<b>√</b>		✓	<b>√</b>			
PJSC «AVTOVAZ»	<b>√</b>	✓	<b>√</b>					
ZMZ	<b>√</b>							

## Typical physical and chemical characteristics

Parameters	Method	Gazpromneft Premium L						
		5W-30	5W-40	10W-40	10W-30	15W-40	20W-50	
Kinematic Viscosity, mm2/s	ASTM D 445							
@ 40°C	AOTH D 440	68,3	90,7	95,6	76,7	107,1	169,3	
@ 100°C		11,78	14,3	14,0	11,6	14,4	18,6	
Viscosity Index	ASTM D 2270	170	164	150	145	138	124	
Flash point (COC), °C	ASTM D 92	224	229	237	240	243	250	
Pour point, °C	ASTM D 97	-41	-42	-42	-44	-37	-29	
Total base number, mg KOH/g	GOST 11362	10,6	9,0	9,3	9,7	9,5	9,3	
Density @ 20°C, kg/m³	ASTM D 4052	851	855	856	854	876	884	
Sulphated ash	ASTM D 874	0,95	1,3	1,2	1,1	1,3	1,0	

The company's management system is certified in accordance with the international standards

**ISO 9001** 



ISO 14001



ISO 45001

